



U.S. Department  
of Transportation  
**Research and  
Special Programs  
Administration**

400 Seventh St., S.W.  
Washington, D.C. 20590

**APR 27 2001**

DOT-E 10962  
(NINTH REVISION)

**EXPIRATION DATE: December 31, 2002**

(FOR RENEWAL, SEE 49 CFR § 107.109.)

1. GRANTEE: ICC The Compliance Center Inc  
Niagara Falls, New York  
(Former grantee: International Compliance Center  
(USA), Ltd.)
2. PURPOSE AND LIMITATIONS:
  - a. This exemption authorizes the manufacture, marking, sale and use of the specially designed combination packagings described herein for transportation in commerce of the materials listed in paragraph 6 without hazard labels or placards, with quantity limits not exceeding one liter for liquids or 2.85 kilograms for solids. This exemption provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein.
  - b. The safety analyses performed in development of this exemption only considered the hazards and risks associated with transportation in commerce.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR §§ 173.13(a) in that Division 5.2 and toxic by inhalation (TIH) materials are included; § 173.13(b) in that passenger-carrying aircraft is authorized for certain materials; § 173.13(c)(1)(ii) in that absorbent material may be placed inside the inner barrier bag; and § 173.13(c)(1)(iv) and § 173.13(c)(2)(iii) in that a protective frame is authorized in place of an inner fiberboard box except as specified herein.
5. BASIS: This exemption is based on the ICC The Compliance Center Inc.'s application dated January 3, 2001, submitted in accordance with § 107.109 and supplemental information dated January 25, 2001 and April 3, 2001.

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

APR 27 2001

| Hazardous Material Description <sup>1</sup> | Hazard Class/Division | Identification Number | Packing Group |
|---|-----------------------|-----------------------|---------------|
| Flammable, liquids                          | 3                     | As Appropriate        | I, II or III  |
| Flammable solids <sup>2,3</sup>             | 4.1                   | As Appropriate        | II or III     |
| Pyrophoric materials <sup>4</sup>           | 4.2                   | As Appropriate        | I             |
| Self heating materials <sup>3</sup>         | 4.2                   | As Appropriate        | II or III     |
| Dangerous When Wet materials                | 4.3                   | As Appropriate        | I, II or III  |
| Oxidizers <sup>4</sup>                      | 5.1                   | As Appropriate        | I, II or III  |
| Organic peroxides <sup>2,3</sup>            | 5.2                   | As Appropriate        | II            |
| Toxic materials <sup>4</sup>                | 6.1                   | As Appropriate        | I, II or III  |
| Corrosive materials                         | 8                     | As Appropriate        | I, II or III  |
| Miscellaneous hazardous materials           | 9                     | As Appropriate        | II or III     |

1 - Only hazardous materials permitted to be transported aboard a passenger-carrying aircraft by column (9A) of the Hazardous Materials Table in § 172.101 are authorized for transport aboard passenger-carrying aircraft; only hazardous materials permitted to be transported aboard a cargo aircraft by column (9B) of the Hazardous Materials Table in § 172.101 are authorized for transport aboard cargo-only aircraft.

2 - Excludes Type A, B and C materials.

3 - Excludes materials which require temperature control.

4 - As restricted by paragraphs 7.c and 7.d.

7. SAFETY CONTROL MEASURES:

a. PACKAGING - Packagings manufactured under this exemption prior to April 30, 2000, are authorized for continued use; However, no new manufacture is authorized. Packagings manufactured after May 1, 2000 must meet the following requirements:

(1) Liquid hazardous material must be placed in a tightly closed glass, metal or plastic inner packaging(s) with a total capacity not exceeding 1.2 liters in volume per completed package. The inner packaging(s) must be sealed and must be compatible with the product. Inner packaging(s) must have sufficient outage so that they will not become liquid full at 55°C. The net quantity (measured at 20°C) in the inner packaging(s) may not exceed one liter;

(2) Solid hazardous material must be placed in a tightly closed glass, metal or plastic inner packaging(s). The net quantity of material in the inner packaging(s) may not exceed 2.85 kilograms. The inner packaging(s) must be sealed and must be compatible with the product;

(3) Inner packaging(s) containing liquid must be:

(i) Surrounded by non-reactive absorbent material, in sufficient quantity to completely absorb the entire contents of the inner packaging(s) and placed into a hermetically sealed (e.g., goose-necked and tied, heat sealed, etc.) barrier bag (4 mils minimum) which is impervious to the lading; or

(ii) Placed into a hermetically sealed barrier bag (4 mils minimum) which is impervious to the lading and surrounded by non-reactive absorbent material in sufficient quantity to completely absorb the entire contents of the inner packaging(s).

(4) The inner packaging(s) (barrier bag and absorbent material, if required) must be placed in a metal can with a sufficient quantity of non-reactive filler material to immobilize the inner packaging(s) and fill all void spaces;

(5) The metal can must be hermetically sealed for APR 27 2001 Division 4.2 and 4.3 materials;

(6) The metal can must be placed in an outer packaging with a protective frame insert which is designed to prevent impact and movement of the metal can. Up to four frame inserts may be placed into an outer package. The outer package must conform to § 173.201 for liquids and § 173.211 for solids.

(7) All closures must be held securely in place by positive means.

b. TESTING -

(1) The completed package, assembled as for transportation and with the inner packaging(s) filled 98% full with liquid, must be successfully tested in accordance with 49 CFR Part 178 at the Packing Group I level.

(2) The metal can with inner packaging(s) filled 98% full, must be successfully tested in accordance with 49 CFR Part 178 at the Packing Group I level. In addition for TIH, and pyrophoric materials, the metal can must be capable of withstanding a pressure differential of 100 kPa.

c. ADDITIONAL SAFETY CONTROL MEASURES FOR A MATERIAL TOXIC BY INHALATION - The following provisions are applicable to materials meeting the definition of "material toxic by inhalation" in § 171.8 that are packaged in accordance with the requirements of this exemption:

(1) Each outside package must be marked "INHALATION HAZARD" in letters at least 12.0 mm (one-half inch) high on a contrasting background in close proximity to the marking specified in paragraph 8.g.

(2) Shipping papers must contain a notation "TOXIC INHALATION HAZARD" in addition to the shipping paper requirements of Subpart C of Part 172.

d. MATERIALS WHICH MAY NOT BE TRANSPORTED BY PASSENGER-CARRYING AIRCRAFT -

(1) Materials which meet the definition of "material toxic by inhalation" in § 171.8 (any zone).

(2) Materials which meet the definition of oxidizer, at the Packing Group I level in accordance with § 173.127(b) (1) (i).

8. SPECIAL PROVISIONS:

a. In accordance with the provisions of Paragraph (b) of § 173.22a, persons may use the packaging(s) authorized by this exemption for the transportation of the hazardous materials specified in paragraph 6, only in conformance with the terms of this exemption.

b. A person who is not a holder of this exemption, but receives a package covered by this exemption, may reoffer it for transportation provided no modifications or changes are made to the package and it is offered for transportation in conformance with this exemption and the HMR.

c. A current copy of this exemption must be maintained at each facility where the package is offered or reoffered for transportation.

d. Each packaging manufactured under the authority of this exemption must be either (1) marked with the name of the manufacturer and location (city and state) of the facility at which it is manufactured or (2) marked with a registration symbol designated by the Office of Hazardous Materials Exemptions and Approvals for a specific manufacturing facility.

e. A current copy of this exemption must be maintained at each facility where the package is manufactured under this exemption. It must be made available to a DOT representative upon request.

f. For transportation by aircraft, the completed package must be offered in conformance with § 173.27(c).

g. MARKING and LABELING

(1) Each package shipped under this exemption must be marked "DOT-E 10962 - NO HAZARD LABELS REQUIRED" in letters at least 12.0 mm (one-half inch) high on a contrasting background in proximity to required DOT markings.

(2) Each package that is offered for transportation by aircraft which contains a material which is not authorized to be transported aboard a passenger-carrying aircraft by column (9A) of the Hazardous Materials Table in § 172.101 must bear a CARGO ONLY AIRCRAFT label.

(3) If the inner metal can is not capable of withstanding a pressure differential of 100 kPa, then the can must be marked in letters at least 6.0 mm (one-quarter inch) high on a contrasting background that the can is not suitable for TIH or Pyrophoric Materials.


9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, rail freight, cargo aircraft only with restrictions (see paragraph 6, note 1), and passenger-carrying aircraft with restrictions (see paragraph 6, note 1 and paragraph 7.d).
10. MODAL REQUIREMENTS: A current copy of this exemption must be carried aboard each aircraft used to transport packages covered by this exemption. The shipper must furnish a copy of this exemption to the air carrier before or at the time the shipment is tendered.
11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this exemption and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:
  - o All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, Parts 171-180.
  - o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this exemption must receive training on the requirements and conditions of this exemption in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this exemption, including display of its number, when this exemption has expired or is otherwise no longer in effect.

12. REPORTING REQUIREMENTS: The carrier is required to report any incident involving loss of packaging contents or packaging failure to the Associate Administrator for Hazardous Materials Safety (AAHMS) as soon as practicable. (Sections 171.15 and 171.16 apply to any activity undertaken under the authority of this exemption.) In addition, the holder(s) of this exemption must also inform the AAHMS, in writing, as soon as practicable of any incidents involving the package and shipments made under this exemption.

Issued in Washington, D.C.



*for* Robert A. McGuire  
Associate Administrator  
for Hazardous Materials Safety

APR 27 2001

(DATE)

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Research and Special Programs Administration, Department of Transportation, Washington, D.C. 20590.  
Attention: DHM-31.

The original of this exemption is on file at the above office. Photo reproductions and legible reductions of this exemption are permitted. Any alteration of this exemption is prohibited.

Copies of exemptions may be obtained from the AAHMS, U.S. Department of Transportation, 400 7th Street, S.W., Washington, DC 20590-0001, Attention: Records Center, 202-366-5046.

PO: RDT/sln